


# Intrinsically Safe Differential Pressure Transmitter



-  II 1 G ATEX Classification
- CENELEC Classification Ex ia IIC T5 Ga
- Accuracy 0.25% of reading
- Ultra low pressure measurement
- Wide span adjustment
- 2-wire, 4-20mA output

**InstruMetrics**  
ENGINEERING

The FCO354 is a fully configurable, Intrinsically Safe IP65 rated low differential pressure transmitter, suitable for industrial applications of control, measurement and monitoring.

The output is scalable as linear to differential pressure or as a square-root function to facilitate the use of Pitot Static Tubes or other primary flow elements.

The large LCD can display a variety of standard engineering units.

The FCO354 can be adjusted from a PC using the FCO301 software utility and cable (in a safe area).

## Features

Models/Ranges	Model1: $\pm 50\text{Pa}$ Model2: $\pm 150\text{Pa}$ Model3: $\pm 500\text{Pa}$	Model4: $\pm 2500\text{Pa}$ Model5: $\pm 10\text{kPa}$ Model6: $\pm 20\text{kPa}$
Output Options	2 wire 4-20mA	
Display (Optional)	Most common differential pressure, volumetric flow, mass flow, and velocity units	
Adjustable Damping	0.0 to 60.0 seconds	
Square Root function	Standard	
Pneumatic Ports	$\frac{1}{4}$ " BSP female fittings and mounting for 54mm centres	

## Performance

Unipolar	10% to 100% range:	$< \pm (0.25\% \text{ reading} + 1 \text{ digit})$
Accuracy @ 20°C	0 to 10% range:	$< \pm (0.025\% \text{ range} + 1 \text{ digit})$
Bipolar	10% to 100% range:	$< \pm (0.5\% \text{ reading} + 1 \text{ digit})$
Accuracy @ 20°C	0 to 10% range:	$< \pm (0.05\% \text{ range} + 1 \text{ digit})$
Span Adjustment	10% to 100% of range	Note: Span can be set anywhere within instruments range. For span $< 20\%$ of range, accuracy is reduced to the bipolar specification
Temperature coefficients	Zero: $< 0.02\%/^{\circ}\text{C}$ Range: $< 0.02\%/^{\circ}\text{C}$	
Working Temperature	$-10$ to $40^{\circ}\text{C}$	
Minimum step response	100ms	
Output Update	50ms	
Long term drift	Typically 0.2% per annum	
Overload	100 x DP range	
Max. Static Pressure	$-1$ to $+10$ bar Gauge	

## Construction

Enclosure	IP65 ATEX rated Aluminium enclosure
Dimensions	166 x 160 x 94mm
Materials in contact with media	Stainless steel, nickel, mica & PTFE
Media Compatibility	Air and non-corrosive gases max 95% humidity non-condensing
Weight	3.5kg

**InstruMetrics**  
ENGINEERING

### Furness Controls Limited

Beeching Road, Bexhill, East Sussex, UK, TN39 3LJ  
Tel: +44 1424 730316 Fax: +44 1424 730317  
Email: [sales@furness-controls.com](mailto:sales@furness-controls.com)  
Web: [www.furness-controls.com](http://www.furness-controls.com)

Furness Controls has a UKAS accredited laboratory which offers pressure calibration from 0 to 40 kPa and flow calibration from 0.1 ml/min to 2000 litres/min

