

MIS Probe 2

Aluminum Oxide
Trace Moisture Probe





Applications

This Panametrics aluminum oxide moisture sensor probe measures moisture concentration in gases and non-aqueous liquids from trace to ambient levels. It is designed to be used with the Panametrics Moisture.IQ analyzer and the PM880 portable hygrometer for industries including:

- Petrochemical
- Natural gas
- Industrial gas
- Semiconductor
- Furnace gas/heat treating
- Power generation
- Air dryer
- Pharmaceutical
- Aerospace

Features

- Intrinsically safe
- Ambient to ppb moisture measurement: 16-bit resolution
- Three function capability with moisture sensor and optional built-in temperature and pressure sensors
- Nonvolatile calibration data storage
- Calibrations traceable to National Institute of Standards and Technology (NIST) or National Physical Lab U.K. (NPL)
- Requires only twisted pair cabling, allowing probe to be located up to 3000 ft (914 m) from analyzer
- Threaded and VCR mount configurations

Panametrics Hygrometer Systems and Moisture Probes

Panametrics aluminum oxide moisture probes have set the standard of performance and value in industrial moisture measurement for more than 50 years.

In use, the Moisture Image Series probe is coupled to Panametrics hygrometer consoles by an interconnecting cable. Ease of use, wide measurement range and rigorous calibration standards make these systems the preferred choice for industrial moisture measurement worldwide.

Built-In Pressure and Temperature Measurement

Accurate determination of many moisture measurement parameters requires knowledge of the process temperature and pressure. The inconvenience and limitations associated with installing and using separate temperature and pressure sensors have been eliminated, with both capabilities being built directly into the Moisture Image Series probe. An NTC thermistor to measure temperature from -22°F to 158°F

(-30°C to 70°C), and a choice of five solid-state piezoresistive transducers to measure pressures up to 5000 psig (345 bar), are available.

Temperature and pressure input data are used by Moisture.IQ analyzers and the PM880 portable hygrometer to determine parameters such as ppm, lbs/mmSCF and relative humidity.

MIS Electronics Module

The real power of the MIS probe comes from an electronic module that is attached to the moisture sensor probe. The built-in microprocessor provides 16-bit resolution, a real performance enhancement, allowing it to detect parts per billion (ppb) changes in moisture concentration. In addition, it continuously monitors and compensates the electronics to ensure long-term stability.

For convenience, moisture probe calibration data is stored in nonvolatile EEPROM, so data entry is automatic and safe from power outage.

The Moisture Image Series probe is intrinsically safe, saving the expense and installation problems associated with explosion-proof housings, purges, or external zener requirements of IEC/Zone 0 areas.



Rigorous Calibration Standards Traceable to the NIST/NPL

The aluminum oxide sensor of each MIS probe is individually calibrated in one of the world's most advanced moisture calibration facilities. Developed over several decades, this facility generates precisely known moisture concentrations, traceable to the NIST/NPL, to which each sensor is exposed during the calibration process.

All data is gathered and stored by a dedicated computer system. Calibrations are repeated over a period of many months to ensure the stability of each individual moisture probe. Only those probes that meet GE's demanding specifications for accuracy and stability are shipped to customers.

Installation Flexibility

The Moisture Image Series probe is designed to be located at the process, exactly where the measurement is needed. The sensor has a wide temperature operating range and can work in process pressures from vacuum up to 5000 psig (345 bar). No minimum flow rate is required. For additional flexibility, the probe can be located up to 3000 feet (0.9 km) from the analyzer, connected by inexpensive, unshielded, cable (AWG 22). As a result, the probe can be placed in the ideal location, even in a large plant, without the cost, delays and installation problems associated with special cabling.

Specifications

Moisture Sensor

Intrinsic Safety

Intrinsically safe when connected to a Panametrics Moisture.IQ analyzer, PM880 portable hygrometer or intrinsically safe barriers in accordance with the user's manual. Moisture Image Series probe:

BAS01ATEX1095

II 1 G Ex ia IIC T4. (-20°C to +80°C) and CSA C US Class I, Division 1, Groups A,B,C&D T4, LR44204-23

European Compliance

Complies with EMC Directive 2004/108/EC and PED 97/23/EC for EN <25

Type

Aluminum oxide moisture sensor probe

Calibration

Each probe is individually computer calibrated against known moisture concentrations, traceable to national standards.

Dew/Frost Point Calibration Ranges

- Overall capability: 140 to -166°F (60 to -110°C) by request
- Standard calibration range: 50 to -112°F (10 to -80°C) with data provided from 68 to -166°F (20 to -110°C)
- Ultralow calibration range: -58 to -148°F (-50 to -100°C) with data to -166°F (-110°C)

Accuracy

- ±3.6°F (±2°C) above -148°F (-100°C)
- ±5.4°F (±3°C) below -148°F (-100°C)

Repeatability

- ±0.4°F (±0.2°C) above -148°F (-100°C)
- ±0.9°F (±0.5°C) below -148°F (-100°C)

Temperature

- Sensor operating temperature (process environment): -166° to 158°F (-110° to 70°C)
- Operating temperature for Moisture Image Series probe electronics module: 32° to 140°F (0° to 60°C)
- Storage temperature: 158°F (70°C) maximum

Operating Pressure

5 µHg to 5000 psig (345 bar).

Limited by optional pressure sensor – see pressure sensor ranges.



Flow Range

- Gases: Static to 10,000 cm/s linear velocity at 1 atm
- Liquids: Static to 10 cm/s linear velocity at density of 1 g/cc

MIS Probe/Analyzer MISP2

3000 ft (0.9 km) maximum recommended length (consult factory for longer distances)

MIS Probe/Analyzer Compatibility

- Moisture.IQ
- PM880 portable hygrometer

MIS Probe/Analyzer Cable

Unshielded, pair, AWG 22

Limited Warranty

- Calibration: Six months from delivery
- Materials and workmanship: One year from delivery

Built-In Temperature Sensor

Type

Nonlinear NTC thermistor (resultant temperature linearized by microprocessor)

Operating Range

- 22° to 158° F (-30° to 70°C)

Accuracy

±0.9°F (±0.5°C) overall

Response Time (Maximum)

One second in well stirred oil or 10 seconds in still air for a 63% step change in increasing or decreasing temperature

Built-In Pressure Sensor

Type

Solid-state/piezoresistive

Available Ranges

- 0-300 PSIG 0-21 Bar(g)
- 0-500 PSIG 0-35 Bar(g)
- 0-1000 PSIG 0-69 Bar(g)
- 0-3000 PSIG 0-207 Bar(g)
- 0-5000 PSIG 0-345 Bar(g)

Accuracy

±1% of full scale

Pressure Rating

Three times the span of the available range to a maximum of 7500 PSIG (518 Bar(g))



panametrics.com

© 2019 Baker Hughes, a GE company, LLC – All rights reserved.

Baker Hughes, a GE company, LLC and its affiliates ("BHGE") provides this information on an "as is" basis for general information purposes and believes it to be accurate as of the date of publication. BHGE does not make any representation as to the accuracy or completeness of the information and makes no warranties of any kind, specific, implied or oral, to the fullest extent permissible by law, including those of merchantability and fitness for a particular purpose or use. BHGE hereby disclaims any and all liability for any direct, indirect, consequential or special damages, claims for lost profits, or third party claims arising from the use of the information, whether a claim is asserted in contract, tort, or otherwise. The Baker Hughes logo is a trade mark of Baker Hughes, a GE company, LLC.

GEA34295

(06/2019)