

GE Infrastructure Sensing

Kaye ValProbe™ is a wire-free process validation and monitoring system designed around the measurement and reporting requirements of the most intensely regulated industries. ValProbe simplifies access to hostile, remote and hard-to-reach environments by eliminating hard-wired sensors, greatly reducing study setup time and associated costs.

The Dual Logger is equipped with two high-accuracy temperature sensors, each capable of capturing 10,000 data points. The dual sensor configuration is ideally suited for measuring penetration and distribution parameters from a single instrument. Precision platinum RTD sensors provide exceptional accuracy and durability. The Dual Logger is available with pairs of bendable or flexible probes, or with a single rigid probe paired with either a flexible or bendable probe.

For the most extreme operating conditions, the Dual Logger is compatible with the low profile Insulating Canister. Designed for use with the bendable probes, the Insulating Canister protects the internal electronics and battery for maximum “time at temperature.”

Kaye ValProbe™ Dual Logger

Applications

- Autoclaves
- Ovens
- Temperature Chambers
- Depyrogenation Tunnels

Features

- Precision Platinum RTD Sensors
- Broad measurement range
- Economical field-replaceable battery
- Operator programmable sample rate, start, delay and stop function



Dual Logger Specifications

Sensing Element	Precision Platinum RTD
Measurement Range and Accuracy	0 to 140°C ± .1°C -45 to 0°C ± .2°C
Environmental	
Temperature	-45 to 140°C
Humidity	0 to 100% humidity, condensing
Pressure	6 Pa to 10 bar absolute
Logger Material	316 stainless steel
Battery	Field-replaceable 3.6V Lithium Thionyl Chloride
Sampling Rate	1 second to 12 hours
Data Storage	10,000 samples per sensor retained in EE PROM memory
Calibration	Factory calibrated (NIST-traceable) with user calibration
Real Time Clock Accuracy	15 seconds per 24 hours (0.0174%) from -45 to 140°C
Regulatory Compliance	UL, CE, Intrinsically Safe

Dual Logger Configurations

1.5" rigid sensor w/ bendable probe (specify length)
Two bendable probes (specify length)
1.5" rigid sensor w/ flexible probe (specify length)
Two flexible probes (specify length)

Insulating Canister

Proprietary insulating materials provide for a compact, low profile design, making the insulating canister suitable for the most demanding thermal validation applications including depyrogenation tunnels and dry heat ovens. For use with Kaye ValProbe bendable and dual readable temperature loggers.

Features

- Proprietary insulating material greatly extends ValProbe operating range
- Low profile design for use in space-restrictive applications (45mm dia. X 149mm long)
- Robust 316 SS construction

Performance

Temperature	Accuracy	Maximum Exposure
360°C	± .5°C	45 min.
300°C	± .5°C	60 min.
250°C	± .2°C	80 min.
200°C	± .2°C	115 min.
170°C	± .2°C	165 min.

Part Number X2545



imagination at work

GE Infrastructure Sensing
1100 Technology Park Drive
Billerica, MA 01821 USA
T: 800 964 5293
sensing@ge.com
www.gesensing.com

©2004 GE Infrastructure Sensing, Inc
All Rights Reserved

PUB 717, REV 1.1 NOV 04 3M